DETAILS OF THE INCIDENT

An employee cement tanker night driver loaded his vehicle and proceeded to the weighbridge. He stopped the vehicle too close to the weighbridge platform and, as a result, the cab door wouldn't open fully as the underside was catching on the platform. Rather than repositioning the vehicle, he attempted to exit the cab forwards and fell / slipped onto the gantry, causing a graze to his leg. The Driver continued with his night shift, not reporting the incident until he arrived at the customer's site. Unfortunately, the driver was absent from work as a result of his injury.

KEY FINDINGS	
	The cabs of the new fleet of Volvos are lower, to

Incident

Reporting

protocol.

aid better vision of vulnerable road users, and Workplace Layout therefore the doors were catching on the walkway platform. Drivers were informed to position their vehicles Safe System slightly further away from the platform so the of Work doors wouldn't catch and they could safely access / egress. Due to the cab door hitting the platform, the driver Get A Grip could not exit the vehicle backwards holding onto the grab handles and chose to step out forwards.

The driver should have reported the incident

Manager in accordance with the reporting

immediately to the Weighbridge or Night Shift

HOW COULD THIS HAVE BEEN AVOIDED

- Review processes to eliminate or reduce the need for drivers to leave their cabs; in this case the site is in a port and port security require the despatch ticket to be stamped with a pass in the weighbridge office.
- As previously instructed, the driver should have repositioned the vehicle when he realised he couldn't open the door fully, enabling him to get out backwards, using both grabrails, giving him 3 points of contact.
- Assess whether any modifications could have been carried out to the platform to overcome the restriction with the doors on the new vehicles.

KEY REVIEW POINTS

- Can systems be revised to minimise the need for drivers to get in / out of their vehicles?
- Where there is a significant change to people, plant or processes, do we have a management of change procedure to reassess the risks and controls?
- Are incident reporting protocols periodically reinforced?

Slight graze to shin



Weighbridge platform



Display Until 19.04.24



Hierarchy of Control

Eliminate

Reduce

Isolate

Control

Protect

Get a grip



Hold handrails on stairways and use three points of contact when getting into/out of

Driving



Drive safely, ensure you are authorised and that vehicles/mobile plant are well

Safe Systems



Follow safe systems of work, site rules, signage and traffic signals.



STOP